



# Technical Data

## OEM Bed Liner Truck Bed Coating



### TYPICAL PROPERTIES

COLORS: black  
CLEANUP: Soap and Water  
VOLUME SOLIDS: 33.5%  
WEIGHT SOLIDS: 42.0%  
VISCOSITY: 2500cps-3000cps  
VOC: 170 g/L  
COVERAGE: 100 to 120 sq. ft./gal.  
Dry Film Thickness: 10 mils to 16 mils  
DRYING TIME: Dry time @ 70°F (21°C); 50% relative humidity  
To Touch: 1 to 2 hours, To Handle: 24 hours, To Recoat: 3 to 4 hours

### Application Information

A gallon of POR-15® OEM Bed Liner will cover approximately 100-120 square feet. This is enough coating to properly apply the recommended 2-coats to all standard-sized 6-foot truck beds.

Apply when air, surface and product temperatures are above 50°F(10°C) and surface temperature is at least 5°F (3°C) above the dew point. Air and surface temperatures must remain above 50°F (10°C) for the next 24 hours. Avoid exterior application late in the day when dew and condensation are likely to form or if rain is expected.

PROTECT FROM FREEZING.

Once applied POR-15® OEM Bed Liner will be ready for light-duty use in 24 hours and regular use in 48 hours.

Application Equipment: Brush; Use a high quality nylon brush. Roller; Use all-purpose short nap shed resistant phenolic core roller.

Clean Up Instructions: Clean hands and all tools using soap and water before POR-15® OEM Bed Liner has dried. Make sure the container lid is securely sealed back on to container. Unused POR-15® OEM Bed Liner can be used at any time.

### Safety Information

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

HEALTH HAZARD INFORMATION: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Can contains Glycol Ether DPM which can be absorbed through skin and cause damage to blood or cause birth defects. May cause skin, eye, nose and throat irritation. Harmful if swallowed.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapor or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

Do not get in eyes, on skin or clothing. Wash thoroughly after handling. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

FOR PROFESSIONAL USE ONLY. NOT FOR RESIDENTIAL USE.  
KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet available from your dealer for further safety and handling information.



Absolute Coatings, Inc.  
38 Portman Rd, New Rochelle, NY 10801  
**800-457-6715**  
**www.AbsoluteCoatings.com**