

Parksafe - Product Specification Sheet



Rear Parking Sensors, Surface mounted

Set of four rear parking sensor with audible buzzer to alert the driver of obstacles when reversing.

Available in Gloss or Matt Black, Silver or White.

Key Specification:

- 4 x 19mm Paint-able Sensors
- Tow bar Ignore Function
- Audible buzzer
- Sensor installation height adjustable
- 12 / 24V DC, 20-200mA
- Power Cable 0.8m
- Sensor Cable 2.5m
- Buzzer cable 2.5m

Additional Specification:

- Detection Range 0.2 - 1.5m
- Frequency 40KHz
- Working Temp. -30°C ~ +70°C

Minimum Install Heights (Approximate) 450 mm

(Vertical mounting surface, potentiometer minimum setting, actual value will vary with increased vehicle load)

Compatible Optional display: PS62 / PS63 / PS64.



PS540



Date Created:

27/10/2022

Specification Sheet
Number:

JAY10010114

Version:

V1.1

Box Dimensions (WxDxH):

250mm x 180mm x 60mm

Approvals & Certifications:

E Mark, CE, UKCA

Box Contents:

4 x parking sensor heads, 4 x parking sensor cables, 1 x control box, 1 x power lead, 1 x buzzer, Velcro pad, cable ties, user manual